




NOTES:

1. Material: UVFS;
2. G - Fine ground surface;
3. All dimensions are in mm;



Isometric view 1:1



Specifications are subject to change without notice  
Dimensions are for reference only

Parameters

| Shape               | Plano                             |
|---------------------|-----------------------------------|
| S1 Surface flatness | $\lambda/10$ @632.8 nm            |
| S1 Surface quality  | 20-10 s/d                         |
| S2 Surface quality  | Commercial polish                 |
| Clear aperture      | $\geq 85\%$                       |
| Protective chamfers | 0.2 - 0.3 mm x 45°                |
| Wedge               | <3 minutes                        |
| Coating             | HR(s+p)/2>99.0%@220-250nm, AOI=0° |



UVFS pl mirror, D=25.4 mm, T=6 mm

| Proprietary                                                                                                                                                       |          | Name | Date       | Part number | Rev. | Scale |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|------|------------|-------------|------|-------|
| The information in this drawing is property of EKSMA Optics. Any reproduction in part or as a whole without the written permission of EKSMA Optics is prohibited. | Approved | A.K. | 2020.01.09 | 082-2225-i0 | A    | 2:1   |
|                                                                                                                                                                   | Drawn    | A.F. | 2020.01.09 |             |      |       |