



NOTES:

1. Material: N-BK7;
2. G - Fine ground surface;
3. All dimensions are in mm;
4. Wedge: <3 min;
5. Protective chamfers: 0.3 mm x 45°;
6. Laser Induced Damage Threshold:
 - > 0.25 J/cm² at @800nm, 50Hz, 94fsec pulses,
 - > 1.8 J/cm² at @1064nm, 50Hz, 11nsec pulses;



Isometric view 1:6



Specifications are subject to change without notice
Dimensions are for reference only

Parameters			 info@eksmaoptics.com www.eksmaoptics.com		N-BK7 pl/cv mirror, D=76.2 mm, T=12.7 mm				
	S1	S2							
Shape	Concave	Plano							
Radius of curvature	1000	Infinity							
Surface flatness	$\lambda/10$ @633nm	λ @633nm per inch	The information in this drawing is property of EKSMA Optics. Any reproduction in part or as a whole without the written permission of EKSMA Optics is prohibited.	Approved Drawn	Name	Date	Part number	Rev.	Scale
Surface quality	40-20 s/d	80-50 s/d			A.K.	2020.11.16	097-0125R-1000	A	1:2
Clear aperture	>90%	>90%			V.S.	2020.11.16			
Coating	Protected silver Ravg>96%@400nm - IR	Uncoated							