	1	2	3	4			5		6		
А	NOTES: 1. Material: Neutral Der 2. G - Fine ground surf 3. Thickness depends of 4. All dimensions are in 5. Protective chamfers: 6. Parallelism: <3 arcm 7. Optical density: 0.6; 8. Transmission: T>250	ace; on material; nm; 0.3 mm x 45°; in;	A-A							А	
Н		A			G						\square
в		0.0	S1 S2							в	
С	Specifications are subje Dimensions are for refe	A A				<u>T</u>				С	
\square	Parameters			MEKSMA							
		S1	S2 Plano	OPTICS		NDAT filter, L=H=50.8 mm, OD=0.6					
	Shape	· · · · · · · · · · · · · · · · · · ·		info@eksmaoptics.com www.eksmaoptics.com							
	Surface flatness	λ @633nm	λ @633nm	Proprietary		Name	Date	Part number	Rev	Scale	D
	Surface quality	60-40 s/d	60-40 s/d		Approved	A.K.	2020.12.10				
	Clear aperture	>90%	>90%	The information in this drawing is property of EKSMA Optics. Any reproduction in part or as a whole without the written permission of EKSMA Optics is prohibited.				240-5606	A	1:1	
	Coating	-	-		Drawn	V.S.	2020.12.10 5]
	I	2	3	4		5			6		